

TANK™ SZ SERIES

TANK SZ 54

TANK SZ 60

DESIGNED FOR PROFESSIONAL DAILY USE ON CHALLENGING TERRAIN. IDEAL FOR PROPERTIES UP TO 20 ACRES.

FEATURES

ZERO-TURN WITH STEERING WHEEL CONTROL AND FOUR WHEEL STEERING

POWER STEERING

54" OR 60" FABRICATED COMMERCIAL-GRADE SLOPED-NOSE DECK

COMMERCIAL-GRADE KAWASAKI® FX SERIES ENGINES

INDUSTRY-LEADING SUSPENSION COMFORT SEAT WITH LUMBAR ADJUST ANGLED BACK AND ARM RESTS

INDUSTRY'S STRONGEST HEAVY-DUTY RAIL FRAME

QUICK-ADJUST STEERING COLUMN

PIVOTING FRONT AXLE

LIMITED 3-YEAR COMMERCIAL WARRANTY* WITH NO HOUR LIMITATION

*See specifications for warranty information.



IT'S NOT JUST THE TOUGHEST COMMERCIAL ZERO-TURN. IT'S THE SMARTEST.

Hills once considered impossible to mow on a zero-turn rider are no match for this commercial zero-turn. With steering wheel control and four-wheel steering, the Cub Cadet TANK SZ offers truly unmatched stability on all types of terrain. Whether you're facing two acres or twenty, it easily delivers a professional-grade cut like never before. There's truly nothing else on earth like the TANK SZ.

SMARTER FEATURES FOR A BETTER EXPERIENCE. THAT'S THE **CUB CADET ADVANTAGE.**



MORE POWER FOR UNMATCHED RESULTS

Kawasaki FX series commercial-grade engines deliver higher horsepower and maximum torque for enhanced performance. Heavy-duty, remote canister air filtration system and premium cooling system provide a durable, long-life design.



INCREDIBLE MANEUVERABILITY AND CONFIDENCE

With unrivaled stability and precision control, there's no terrain the TANK SZ can't handle. Steering wheel control and four-wheel steering gives more confidence on hills than ever before. By delivering a quality cut at angles other riders can't handle, it's easy to see what makes the TANK SZ the smartest choice in commercial zero-turns.



UNBEATABLE CORROSION PROTECTION AND DURABILITY

Provides twice the protection against unforgiving environmental conditions while ensuring even the most complex parts are thoroughly and evenly coated inside and out with an electronically-applied dual layer of eCoat and powder. Now that's a smart investment.



YOUR INDEPENDENT DEALER – EXPERT SERVICE. LOCALLY OWNED. THE ADVICE, SELECTION AND SUPPORT YOU NEED TO FIND THE RIGHT FIT IS AT YOUR LOCAL CUB CADET DEALER.

ATTACHMENTS

THAT BOOST PRODUCTIVITY
ALL YEAR ROUND

Whether you're working through the heat of summer or the dead of winter, our attachments are made to boost your earning potential the whole year through. So you can maximize your profits while getting the best results possible.



POWER LIFT



TRIPLE BAGGER/DUMP HOPPER WITH POWER ASSIST



12-VOLT OUTLET KIT



LIGHT KIT



ULTRA TRACTION TIRE/RIM



72" SNOW BLADE

ALSO AVAILABLE:

- MULCH KIT
- CASTER WHEEL KIT

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.

* As rated by Kawasaki, horsepower tested in accordance with SAE J1995 and rated in accordance with SAE J2723 and certified by SAE International
† See your local Cub Cadet Independent Dealer for warranty details.

Cub Cadet commercial products are intended for professional use.
773-05501 Printed in U.S.A. 1/14 © 2014 Cub Cadet

| ENGINE | TANK SZ 54 | TANK SZ 60 |
|---------------------------------|---|------------|
| Engine Type | Commercial-grade Kawasaki® FX Series V-Twin OHV | |
| Engine Displacement/Orientation | • 852cc/Vertical • | |
| Engine Horsepower | • 27 HP* • | |
| Engine Fuel | • Gasoline • | |
| Lubrication/Filter | • Full pressure w/ spin-on filter • | |
| Cooling System | • Air • | |
| Air Cleaner | • Heavy-duty canister air filter • | |
| Alternator | • 12V - 20 amp regulated • | |
| Fuel Capacity | • Twin 7.5-gal. tanks (15-gal. total) • | |
| Fuel Gauge | • Standard (mounted on tank) • | |

DRIVE SYSTEM

| | | |
|--------------------------|--|--|
| Drive System | PARKER™ Torqpack 14cc pumps and 280cc wheel motors | |
| Ground Speed | • Fwd: 11 mph/Rev: 5 mph • | |
| Hydraulic Fluid | Castrol Edge w/ Syntec Power 5W-50 | |
| Hydraulic Fluid Capacity | • 7 qt. total • | |
| Hydraulic Oil Filter | • Individual filter cartridges standard • | |
| Controls | • Quick-adjust steering column • | |
| Return to Neutral | • Standard • | |
| Braking/Parking Brake | • Dynamic drum, hand lever control • | |

STEERING

| | |
|-----------------------------|--|
| Caster Wheel Pivot Bearings | • Tapered roller, greasable • |
| Front Axle | Pivoting, steerable front wheel w/ cast-iron |

CHASSIS

| | |
|-------|---|
| Frame | Heavy-duty rail frame 3/8" x 5" laser cut steel w/ tie-down slots |
|-------|---|

TIRES

| | |
|-----------------|--|
| Front Tire Size | • 15" x 6.5" - 8" (turf) • |
| Rear Tire Size | 24" x 12" - 12" (turf) (wide track, smart traction tread/self clean) |

DIMENSIONS

| | | |
|---------------------|-----------------------|---------------------|
| Length/Width/Height | 86.5" / 49.5" / 73.5" | 86.5" / 61.5" / 74" |
| Wheelbase | • 54" • | • 54" • |
| Front Track Width | • 43" • | • 43" • |
| Rear Track Width | 50" | 52" |
| Weight (approx.) | 1,250 lbs. | 1,300 lbs. |

MOWER DECK

| | | |
|---|---|-----------------|
| Deck Size/Type | 54" sloped-nose | 60" sloped-nose |
| Deck Style/System | • Floating • | |
| Deck Blades | Triple-blade/High-lift blade (standard) | |
| Deck Construction | 10-gauge fabricated with 7- and 10-gauge reinforcements | |
| Deck Drive | • Belt - Kevlar® B-section • | |
| Deck Lift | • Single pedal, spring-assisted • | |
| Deck Height Adjustment | • 1" - 5" (in .25" increments) • | |
| Blade Spindle Construction | • Cast-aluminum • | |
| Deck PTO | • Electronic fingertip engagement • | |
| Front Anti-Scalping Wheels/ Nose Roller | • 2 standard, greasable/2-nose wheels • | |
| Rear Anti-Scalp Rollers/Striper | • Full width, adjustable w/ stability rod • | |

ADDITIONAL SPECIFICATIONS

| | |
|---------------------|---|
| ROPS | Standard, foldable/2-position lock (ISO 21299, OSHA 1928) |
| Monitor/Hour Meter | • Standard • |
| Seat Type | High-back, premium suspension with lumbar adjust angled back and Elasticity Vibration Control (EVC) comfort control seat w/ arm rests |
| Cup Holder | • Standard • |
| Storage Box | • Standard • |
| Rear Bumper & Hitch | Heavy-duty rear bumper w/ hitch standard |

WARRANTY†

| | |
|--|---|
| | 3-year limited commercial warranty (no hour limitation) |
|--|---|